

The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your floorcovering. **Regular cleaning is more beneficial to the floorcovering and more cost-effective than occasional heavy cleaning.**



APPLICATION OF A FLOOR DRESSING

Using an applicator and tray, or mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the skirtings. It should then be left to dry. This normally takes approximately thirty minutes, depending on the ambient conditions and the thickness of the coating.

When the first coat is dry, a second coat should be applied at right angles to the direction of the first. Subsequent coats should be applied at right angles, and the final coat should be applied right up to the skirting.

Two to three thin coats are usually sufficient to provide excellent resistance to abrasion, scuffing and removal of black heel marking. However, be guided by your own periodic assessments for the particular location.

In order to minimise costs, subsequent polish applications may be applied only to traffic paths.

Periodically – generally every six months – assess the appearance of the floor. If there is an unacceptable build-up of polish, this should be stripped and reapplied, as per the instructions above.

NOTES

Always follow the Health and Safety guidance provided, and dilute cleaners and detergents in accordance with the manufacturers' instructions. For further information, contact Cavalio Customer Technical Services on +44 (0)845 345 5404, or email tech@cavaliofloors.com. At the date of issue the data presented is correct. However, Cavalio Floors reserve the right to make changes which do not adversely affect performance or quality.

INITIAL CONSTRUCTION CLEAN

- ✓ Remove all loose debris.
- ✓ Ensure that all traces of adhesive are removed from the surface of the floorcovering.
- ✓ Mop sweep or vacuum to remove dust and grit.
- ✓ Damp mop with a neutral detergent.
- ✓ If required, dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.

ROUTINE MAINTENANCE

The following recommendations are provided as a guideline, and the frequencies can be changed to optimise the appearance.

DAILY

- ✓ Mop sweep or vacuum to remove dust and loose dirt.
- ✓ If required, spot clean to remove stubborn marks with a neutral cleanser.
- ✓ If required, dry buff to restore finish.

WEEKLY/MONTHLY

- ✓ Assess the appearance of the floor.
- ✓ If required, scrub with a scrubber dryer fitted with suitable pads, and using neutral cleanser (pH 7 to 9).
- ✓ If required, dry buff to restore finish.