

CAVALIO

EXCEPTIONALLY STYLISH FLOORS

CONCEPTLINE



PROJECTLINE



NEW

PROJECTLINE
SHADES
also available in
LOC



2882 MISTED CONCRETE & 2863 BRUSHED OAK, MEDIUM

CAVALIO COLLECTION OVERVIEW	4
CONCEPTLINE	
Introduction	6
Collection	8
Shades at a Glance	24
Accessories	27
PROJECTLINE & LOC	
Introduction	28
LOC in More Detail	30
Collections	32
Shades at a Glance	50
Accessories	54
CAVALIO Essentials	
Design Floors	56
LOC Installation Guide	58
Technical Specification	60
Floorcare	62

CAVALIO

EXCEPTIONALLY STYLISH FLOORS

COLLECTION OVERVIEW

Cavalio brings stunning flooring solutions to any interior with three distinct collections; **CONCEPTLINE**, **PROJECTLINE** & **LOC**. The fantastic array of designs on offer, along with a combination of product durability and installation methods, ensure Cavalio is the ultimate vinyl flooring choice.

The Cavalio collection successfully reflects the appeal of natural materials alongside the resilience of vinyl flooring. Each collection features eye-catching designs that portray classic and aged woods; natural stones and man-made materials.

CONCEPTLINE offers effortless style created by our design experts to complement contemporary interior trends. The beauty of the **PROJECTLINE** & **LOC** collections is they offer the same alluring designs but with a choice between installation methods.

With such comprehensive options on offer, we are confident you will find the perfect design and flooring solution for your project.

WHERE TO BUY >>

Find your nearest store on cavaliofloors.com
or get in touch with Cavalio on 0845 345 5404

WHAT'S THE DIFFERENCE?

Both **CONCEPTLINE** and **PROJECTLINE** are traditional Luxury Vinyl Tiles which are secured in place with adhesive.

LOC uses a patented locking system which eliminates the need for adhesive and means the floor can be walked on immediately. Installation time is reduced by up to half, making **LOC** ideal for a wide range of quick turnaround projects.

	Wear Layer (mm)	Domestic	Light Commercial	Heavy Commercial
CONCEPTLINE	0.3	•	•	
PROJECTLINE	0.55	•	•	•
LOC	0.55	•	•	•





CONCEPTLINE

2.00mm | 0.3mm



Featuring 24 stunning designs, **CONCEPTLINE** has been developed by a team of design experts to inject style into your home interior. Laid in a wide variety of patterns, take inspiration from our inventive photography and envisage your favourite shade laid in your space.

A durable 0.3mm protective wear layer is a perfect choice for every room in the home, as well as light commercial interiors.

3025 CLASSIC OAK, WAXED (page 19)

WHERE TO BUY >>

Find your nearest store on cavaliofloors.com
or get in touch with Cavalio on 0845 345 5404



3497 184.2 x 1219.2mm



3489 152.4 x 1219.2mm



3499 184.2 x 1219.2mm



NORDIC OAK, WHITE



DRIFTWOOD, LIGHT



GREY BEAM



3494 184.2 x 1219.2mm



3037 184.2 x 1219.2mm



WEATHERED ASH



LIMED OAK, GREY





3027 152.4 x 914.4mm



3496 184.2 x 1219.2mm



3474 184.2 x 1219.2mm



GREY ASH



NORDIC OAK, HONEY



VINTAGE OAK, GREY



3477 184.2 x 1219.2mm



3492 184.2 x 1219.2mm



3032 152.4 x 914.4mm



COUNTRY OAK, BLOND



LIMED OAK, HONEY



CLASSIC OAK



3035 184.2 x 1219.2mm



3046 152.4 x 914.4mm



3472 184.2 x 1219.2mm



CHESTNUT OAK



RUSTIC OAK, GOLD



VINTAGE OAK, BROWN



3504 184.2 x 1219.2mm



3038 184.2 x 1219.2mm



3025 152.4 x 914.4mm





3051 304.8 x 609.6mm



3057 304.8 x 609.6mm



3556 304.8 x 609.6mm



3053 304.8 x 609.6mm



NATURAL SANDSTONE



SCOTTISH SLATE



CHALKED LIMESTONE



GREY SLATE



3555 304.8 x 609.6mm



3508 152.4 x 914.4mm



ORGANIC LIMESTONE




LIGHT GREY CEMENT



WARM GREY CEMENT

152.4 x 914.4mm



Grey Ash 3027



Classic Oak, waxed 3025




Classic Oak 3032



Rustic Oak, gold 3046

152.4 x 1219.2mm



Driftwood, light 3489

184.2 x 1219.2mm



Limed Oak, honey 3492



Nordic Oak, honey 3496



Country Oak, blond 3477

- Bevelled Edge*
- High shade variation


184.2 x 1219.2mm



Vintage Oak, grey 3474



Nordic Oak, white 3497




Grey Beam 3499



Weathered Ash 3494



Limed Oak, grey 3037



Limed Oak, brown 3038



Washed Pine, dark 3504



Vintage Oak, brown 3472



Chestnut Oak 3035

* Please note bevelled CONCEPTLINE designs cannot be paired with Inlay Accessories

CONCEPTLINE STONES

304.8 x 609.6mm



Chalked Limestone **3556**




Natural Sandstone **3051**



Organic Limestone **3555**




Scottish Slate **3057**



Grey Slate **3053**

152.4 x 914.4mm



Warm Grey Cement **3507**



Light Grey Cement **3508**

Bevelled Edge — Please note bevelled CONCEPTLINE designs cannot be paired with Inlay Accessories.

CONCEPTLINE INLAY ACCESSORIES

Cavalio offers a wide choice of creative Inlay Accessories which are compatible with CONCEPTLINE. Designed to complement the entire collection* – the creative combinations are endless.

FEATURE STRIPS

Inlay strips in solid colours



0032 Cream feature strip with **3497** Nordic Oak, white

5 x 1000mm	
	0025
	0028
	0031
	0032

MARQUETRY STRIPS

Authentic wood effect inlay strips



2056 Maple & **2059** Walnut marquetry strip with **3046** Rustic Oak, gold

3 x 914mm	
	2056
	2057
	2058
	2059

GROUTING STRIPS

Creative and natural grout line effects



2039 Graphite grouting strip with **3051** Natural Sandstone

3 x 914mm	
	2031
	2033
	2035
	2037
	2039



1011 Classic Oak & **1012** Walnut (10mm) Cross Grain Marquetry Strips with **3035** Chestnut Oak

CROSS GRAIN MARQUETRY STRIPS

Wood effect inlay strips with grain at 90° to the main floor area

10 x 914mm	
	1011
	1012
25 x 914mm	
	2511
	2512

Bespoke inlay strips are available by special order in any unbevelled shade and will be cut to required width from the chosen plank or tile.

* Please note bevelled CONCEPTLINE designs cannot be paired with Inlay Accessories.

PROJECTLINE

2.50mm | 0.55mm

LOC

4.50mm | 0.55mm



Featuring 24 stunning designs, **PROJECTLINE** & **LOC** help to inspire an appealing sense of luxury. Offering a mix of classic and contemporary designs, take inspiration from our inventive photography to envisage your favourite shade laid in your space.

A superior 0.55mm protective wear layer is engineered to meet the demands of heavy commercial interiors, whilst also being highly suitable for all areas of the home.

WHERE TO BUY >>

Find your nearest store on cavaliofloors.com
or get in touch with Cavalio on 0845 345 5404

2912 VINTAGE WOOD, BEIGE (page 37)

LOC features interlocking vinyl planks and tiles that are available across all 24 of the PROJECTLINE shades.


This patented system eliminates the need for adhesive, therefore reducing installation time by half, and when laid with the recommended Cavalio LOC underlay offers up to 19dB impact sound reduction.

The authenticity of LOC is further enhanced with a micro bevel effect on each of the 4 edges of the plank or tile – adding subtle depth and realism to the finished installation.

Featuring a superior 0.55mm wear layer, LOC is extremely durable; suitable for residential, light commercial and heavy commercial spaces.

LOC

4.50 mm | 0.55 mm



Refer to page 58-59 for Installation Guide



CAVALIO LOC UNDERLAY

- ✓ Easy to install
- ✓ Smooths minor subfloor imperfections
- ✓ Improved comfort underfoot
- ✓ 19dB impact sound reduction
- ✓ Low water absorption of less than 1% avoiding the growth of mould & mildew
- ✓ Suitable for underfloor heating



2872 WASHED PINE, GREY (refer to page 37)



2946 PROJECTLINE 184.2 x 1219.2mm




2839 PROJECTLINE 184.2 x 1219.2mm




2935 PROJECTLINE 152.4 x 1219.2mm



2864 LOC 177.4 x 1212.4mm



2875 LOC 177.4 x 1212.4mm



2867 LOC 145.6 x 1212.4mm





2966 PROJECTLINE 184.2 x 1219.2mm

2861 LOC 177.4 x 1212.4mm



1942 PROJECTLINE 152.4 x 914.4mm

2856 LOC 145.6 x 907.6mm



2841 PROJECTLINE 184.2 x 1219.2mm

2876 LOC 177.4 x 1212.4mm






2938 PROJECTLINE 184.2 x 1219.2mm

2866 LOC 177.4 x 1212.4mm 




2912 PROJECTLINE 184.2 x 1219.2mm

2862 LOC 177.4 x 1212.4mm 



2836 PROJECTLINE 184.2 x 1219.2mm

2872 LOC 177.4 x 1212.4mm 



VINTAGE OAK, DARK GREY



VINTAGE WOOD, BEIGE 



WASHED PINE, GREY 



2838 PROJECTLINE 184.2 x 1219.2mm

2874 LOC 177.4 x 1212.4mm 



2837 PROJECTLINE 184.2 x 1219.2mm

2873 LOC 177.4 x 1212.4mm 




2842 PROJECTLINE 184.2 x 1219.2mm

2877 LOC 177.4 x 1212.4mm 






2968 PROJECTLINE 184.2 x 1219.2mm 

2858 LOC 177.4 x 1212.4mm 



LIMED OAK, LIGHT



2834 PROJECTLINE 184.2 x 1219.2mm 

2869 LOC 177.4 x 1212.4mm 



FRENCH OAK, BLOND



2965 PROJECTLINE 184.2 x 1219.2mm

2863 LOC 177.4 x 1212.4mm



2907 PROJECTLINE 152.4 x 914.4mm

2859 LOC 145.6 x 907.6mm



2833 PROJECTLINE 184.2 x 1219.2mm

2868 LOC 177.4 x 1212.4mm



BRUSHED OAK, MEDIUM



CLASSIC OAK




WILD NATURAL OAK



2944 PROJECTLINE 184.2 x 1219.2mm

2865 LOC 177.4 x 1212.4mm 



2835 PROJECTLINE 184.2 x 1219.2mm 

2871 LOC 177.4 x 1212.4mm 




1944 PROJECTLINE 152.4 x 914.4mm


2857 LOC 145.6 x 907.6mm 





2845 PROJECTLINE 457.2 x 914.4mm 

2882 LOC 298.0 x 602.8mm 



2846 PROJECTLINE 457.2 x 914.4mm 

2883 LOC 298.0 x 602.8mm 



MISTED CONCRETE



ORIGINAL CONCRETE

2847 PROJECTLINE 457.2 x 914.4mm

2884 LOC 298.0 x 602.8mm

2926 PROJECTLINE 457.2 x 914.4mm

2881 LOC 298.0 x 602.8mm



INDUSTRIAL CONCRETE




BLACK METALSTONE

PROJECTLINE WOODS

184.2 x 1219.2mm

LOC WOODS

177.4 x 1212.4mm




Vanilla Oak 2839 2875



Vintage Oak, grey 2946 2864



Grey Stained Pine 2841 2876



Vintage Oak, dark grey 2938 2866



Limed Oak, grey 2966 2861



Washed Pine, grey 2836 2872



Washed Pine, charcoal 2838 2874




Washed Pine, brown 2837 2873


* Bevelled PROJECTLINE designs should be paired with CONCEPTLINE Inlay Accessories

† Please note LOC designs cannot be paired with Inlay Accessories

PROJECTLINE Bevelled Edge* LOC Micro Bevel† Design features high shade variation



Limed Oak, light 2968 2858



French Oak, blond 2834 2869




Vintage Wood, beige 2912 2862




Brushed Oak, medium 2965 2863




Rustic Oak, brown 2842 2877



Authentic Rustic Oak 2944 2865



French Oak, smoked 2835 2871




Wild Natural Oak 2833 2868

PROJECTLINE WOODS
152.4 x 1219.2mm

LOC WOODS
145.6 x 1212.4mm

PROJECTLINE Bevelled Edge* LOC Micro Bevel† Design features high shade variation




Grey Elm 2935 2867

PROJECTLINE WOODS
152.4 x 914.4mm


LOC WOODS
145.6 x 907.6mm



Driftwood, grey 1942 2856



Classic Oak 2907 2859



Driftwood, dark 1944 2857

PROJECTLINE STONES
457.2 x 914.4mm

LOC STONES
298.0 x 602.8mm



Misted Concrete 2845 2882



Industrial Concrete 2847 2884



Original Concrete 2846 2883



Black Metalstone 2926 2881

* Bevelled PROJECTLINE designs should be paired with CONCEPTLINE Inlay Accessories
† Please note LOC designs cannot be paired with Inlay Accessories

PROJECTLINE INLAY
ACCESSORIES

Cavalio offers a wide choice of **PROJECTLINE** Inlay Accessories allowing you to create a truly unique design floor.

PROJECTLINE Inlay Accessories are available to enhance any non-bevelled wood or stone design. For bevelled designs refer to **CONCEPTLINE** inlay accesories on page 27.

MARQUETRY STRIPS

Authentic wood effect inlay strips

5 x 914mm	
Light Oak	2551
Mid Oak	2552
Walnut	2553

FEATURE STRIPS

Inlay strips in solid colours

5 x 1000mm	
Silver	5100
Black	5103
Brown	5110

CROSS GRAIN MARQUETRY STRIPS

Wood effect inlay strips with grain at 90° to the main floor area

10 x 914mm	
Mid Oak	1021
Walnut	1022

GROUTING STRIPS

Creative and natural grout line effects

5 x 914mm	
Beige	2537
Grey	2536
Black	2538

25 x 914mm	
Mid Oak	2521
Walnut	2522

Bespoke inlay strips are available by special order in any unbevelled shade and will be cut to required width from the chosen plank or tile.

Please note **LOC** designs cannot be paired with Inlay Accessories



2553 Walnut & 2551 Light Oak marquetry strips with 2907 Classic Oak

DESIGN FLOORS — WOOD

Beautifully intricate design floors can be crafted from Cavalio wood designs. Choose from either a standard floor layout or a more ambitious custom design. Most ideas can be achieved with the help of Cavalio's bespoke cutting service.

These linear drawings illustrate a selection of creative designs to help inspire when choosing your new Cavalio floor.






Cut third length herringbone*



Cut third length tramlines*



Full plank tramlines



DESIGN FLOORS — STONE

Cavalio stone designs are highly versatile when individually laid or paired with a complementary or contrasting design. The possibilities are endless and truly unique palettes and patterns can be created to suit your interior surroundings.

Take inspiration from the below creative designs and envisage your new Cavalio floor.






Rectangular tile – brickwork with strip



Dual width tiles with strip*
Typically cut 1/2 & 1/4 tiles lengthways



Bespoke design floor†



BESPOKE CUTTING


*Basic cutting †Bespoke complex cutting
Speak to your flooring provider for more details.

WHERE TO BUY >>

Find your nearest store on cavaliofloors.com
or get in touch with Cavalio on 0845 345 5404


LOC INSTALLATION INSTRUCTIONS

We recommend that your new **LOC** floor is fitted by a professional flooring installer over the recommended Cavalio **LOC** underlay. This is designed to prevent the planks or tiles from sliding or becoming damaged due to unevenness in the subfloor. For more detailed installation instructions, including subfloor preparation and conditioning, please refer to the Cavalio Technical Guide.




FIRST TILE or PLANK, FIRST ROW

The boards are laid without glue/adhesive. Start to lay the floor in the left-hand corner of the room. A minimum expansion gap of 4mm should be left around the installation perimeter and anything protruding from the subfloor. For larger installations an expansion gap of 1mm per linear metre of room length should be used. e.g. a room 8m x 4m would require an expansion gap of 8mm around the entire perimeter of the room and around anything protruding from the floor. **Use small offcuts of the tile/plank as spacers between the planks and the walls to help achieve the correct size gap.**




LAST TILE or PLANK, FIRST ROW

Insert correct sized spacer between the end of the first row and the wall to ensure the correct expansion gap is left. Measure the length of the last tile/plank to fit. Cut the last panel to correct length, recommended minimum length is 350mm.




SECOND TILE or PLANK, SECOND ROW

Press the short end of the next tile/plank at an angle to the first one, and then lay down. Complete the first row in the same way.



FIRST TILE or PLANK, SECOND ROW


Insert spacer between the end of the first row and the wall (expansion gap). Start the new row with the leftover piece from the last row. Insert the tile/plank at an angle against the plank in the previous row, press forward and fold down at the same time. Always try to stagger the short joints approx. 150mm from a short joint in the previous row.



MANAGING UNEVEN WALLS

If the wall is uneven, the floorboards should be marked or scribed to its contours. Mark the floorboards with the contour of the wall. Don't forget to include the required expansion gap to the wall.

To cut the planks to fit the last row, position them one at a time directly over the previous row in the direction you'll be laying them. Hold them firmly in place. Then line up a third board on top. Use the edge of this board to mark the cutting line with a pencil on the board beneath. **Remember to allow for the expansion gap.**




DOOR FRAMES

When installing Interlocking plank/tile around a door frame, cut into the door frame with a handsaw, using an off cut plank/tile and some underlay as a guide for the height and the amount to trim off the door frame. Slide the cut piece under the door frame.


ADJOINING OTHER FLOOR COVERINGS

When adjoining other floor coverings, finish the Interlocking plank/tile in the doorway. An appropriate expansion gap should be left between the Interlocking plank/tile and the adjoining floor covering. This can be covered using a suitable threshold or diminishing strip later.




RADIATOR PIPES (Fig.6 & 7)

Principle cut out — mark the centre of the holes on both the long and short sides using a carpenter's square and a pencil. Where the marks cross drill a pilot hole using a thin #6 or #8 drill bit. Further drill the hole with a spade bit wide enough to accommodate both the diameter of the pipe and the required expansion gap. Cut around as shown with a saw or with a sharp utility knife. Install the floor plank. If necessary, put a bead of contact glue on the cut piece and replace.



Insert a spacer directly behind the inserted piece to wedge it in place ensuring that the correct sized expansion gap has been left. Leave this in place until the glue has hardened.



INSTALLING ACROSS MULTIPLE ROOMS

Finish the Interlocking plank/tile in the doorway on either side and allow a break between the two floors of double that left around the perimeter.

A suitable threshold strip can then be installed to cover the resultant gap. **Place two small off cut pieces of Interlocking plank/tile back to back to gauge the correct gap size.**

When installing a threshold never mechanically fix direct to the Interlocking plank/tile; instead affix to the sub-floor and allow sufficient space between the top edge of the threshold and the surface of the Interlocking plank/tile so as to allow movement into the expansion gap.

COMPLETION WORK

Interlocking planks/tiles are designed as floating floors hence the floor covering can be walked on directly after it is installed. Remove all the spacers and wedges from the edge expansion gaps.

Skirting boards, base boards, quadrants or scotia can be used to conceal the expansion gap, however they should never be fitted directly onto the surface of the interlocking plank/tile. **Leave a small gap between the two, allowing for the natural movement of the plank underneath the skirting or scotia.**

VISIT OUR WEBSITE

cavaliofloors.com

Cavalio has a designated website which is packed full of useful links and further information to help you choose the perfect flooring solution for your interior.

FREE SAMPLES SERVICE

Free samples can be ordered online or by calling our Cavalio Sample Service Team on **0845 345 5405**.

OUR ENVIRONMENT

As a manufacturer of high design and high-performance flooring collections, Cavalio are committed to minimising the impact of our products on the environment throughout their entire life. Cavalio's technical processes are continuously assessed to ensure our goals are met, providing confidence in being able to offer our customers the best possible quality whilst remaining environmentally focused.

The increasing awareness and attention to sustainable development is a key aspect of manufacturing and as such, each Cavalio product is 100% recyclable and contains an average of 40% recycled content. We have achieved SA 8000 approved factory status, providing social accountability throughout our manufacturing process as well as receiving ISO 14001 approval for environmental management. Along with low VOCs, energy efficient manufacturing, long life and low maintenance it is clear why Cavalio achieves BRE A+ for its LCA performance.

An Environmental Product Declaration (EPD) is available upon request which is an independent, third party assessment of our environmental credentials, set out in a transparent format.

Collectively, the socially accountable manufacturing, recyclable suitability, low VOCs and transparent credentials present a sustainable environmental package. For further details on any technical or environmental data, please contact Cavalio on **0845 345 5404**.

Choosing an environmentally preferable product from Cavalio means no compromise in the function and performance of the product.

100%
RECYCLABLE

40%
AVERAGE CONTENT OF
RECYCLED MATERIAL

LOW
VOC

SA 8000
APPROVED
FACTORY

ISO 14001
ENVIRONMENTAL
MANAGEMENT

TECHNICAL SPECIFICATION

CHARACTERISTICS	STANDARD	CONCEPTLINE	PROJECTLINE	LOC
Type of floor covering	EN ISO 10582	heterogeneous, PVC	heterogeneous, PVC	heterogeneous, PVC
Surface treatment		PU	PU	PU
Total weight	EN ISO 23997	3600 g/m²	4290g/m²	8600g/m²
Performance classification	EN ISO 10874	23 / 31	23 / 33 / 42	23 / 33 / 42
Gauge	EN ISO 24346	2.0 mm	2.5mm	4.5mm
Wear layer thickness	EN ISO 24340	0.3 mm	0.55mm	0.55mm
Packaging plank / tile size	EN ISO 24342	24 @ 152.4 x 914.4mm = 3.34m² 18 @ 152.4 x 1219.2mm = 3.34m² 15 @ 184.2 x 1219.2mm = 3.37m² 18 @ 304.8 x 609.6mm = 3.34m²	24 @ 152.4 x 914.4mm = 3.34m² 18 @ 152.4 x 1219.2mm = 3.34m² 15 @ 184.2 x 1219.2mm = 3.37m² 8 @ 457.2 x 914.4mm = 3.34m²	15 @ 145.6 x 907.6mm = 1.98m² 11 @ 145.6 x 1212.4mm = 1.94m² 9 @ 177.4 x 1212.4mm = 1.94m² 11 @ 298.0 x 602.8mm = 1.98m²
Dimensional stability	EN ISO 23999	≤ 0.15%	≤ 0.15%	≤ 0.15%
Residual indentation	EN ISO 24343-1	≤ 0.1mm*	≤ 0.1mm*	≤ 0.1mm*
Colour fastness to artificial light	EN ISO 105-B02	≥ 6	≥ 6	≥ 6
Behaviour to fire	EN 13501-1	Bfl - s1	Bfl - s1	Bfl - s1
Slip resistance**	DIN 51130 EN 13893	R10 DS	R10 DS	R10 DS
Impact sound reduction	EN ISO 10140-3	2 dB	2 dB	3 dB
Resistance to thermal conductivity	EN 12667 ISO 8302	0.02 m²k/w	0.02m²k/w	0.02m²k/w
Static electrical propensity	EN 1815	< 2 kV	<2 kV	<2 kV
Chemical resistance	EN ISO 26987	***	***	***
Abrasion resistance	EN ISO 10582	Type I	Type I	Type I
Castor chair suitability	ISO 4918	yes, type W, EN 12529	yes, type W, EN 12529	yes, type W, EN 12529
Underfloor heating suitability	EN 1264-2	suitable, max. 27 °C	suitable, max. 27 °C	suitable, max. 27 °C
VOC emissions		AgBB - very low emissions Eurofins - Indoor Air Comfort Gold	AgBB - very low emissions Eurofins - Indoor Air Comfort Gold	AgBB - very low emissions Eurofins - Indoor Air Comfort Gold
Applications		Ideal for use in any domestic situation and light to moderate commercial areas	Ideal for use in any heavy commercial areas within the retail, office, leisure, healthcare, education and housing sectors	

* Average test value from current production.
** For clarification regarding slip, consult Cavalio.
*** Resistant depending on concentration and time of exposure. In case of increased impact of oils,grease, acids, alkalis and other aggressive chemicals, please contact us.

FLOORCARE

All planks and tiles in the Cavalio collection feature a polyurethane surface treatment to help protect your floor from everyday wear, ensuring the optimum long-term performance of your floor. To keep your Cavalio floor looking as good as the day it was installed, we recommend you follow the below floorcare guidelines.

RESIDENTIAL AREAS

Day to Day Cleaning:

- ✓ Install a good quality entrance mat by exterior doors to collect loose dirt and grit
- ✓ The application of a suitable floor polish is advisable to assist with ongoing maintenance
- ✓ Sweep or vacuum your floor every day
- ✓ Regularly use a fresh mop and neutral cleaning solutions to evenly clean your floor. Remember to collect and dispel all excess fluid into your mop bucket
- ✓ Address spillages as soon as you can to reduce the risk of staining or causing slips
- ✓ Insert protective pads and cups under furniture to protect your floor from scratches and indentations
- ✓ Regularly trim your pets claws to help avoid scratching
- ✗ Drag furniture with unprotected feet across the floor
- ✗ Use abrasive liquids or metal scouring pads to aid cleaning as these can damage the floor
- ✗ Clean the floor with solvents, caustic detergents, washing up liquids, soap powders, bleach, furniture polishes, petroleum based products, pine gels, stain removers or highly coloured products. Such products may make the floor slippery or cause permanent damage.

COMMERCIAL AREAS

For commercial floorcare instructions contact Cavalio on **0845 345 5404** or visit **cavaliofloors.com**



ANYMORE QUESTIONS?

For general information on your specific project, speak with your local Cavalio provider. If you require detailed technical data, contact Cavalio on **0845 345 5404** or email **info@cavaliofloors.com**

CAVALIO

EXCEPTIONALLY STYLISH FLOORS

CAVALIO UK & IRELAND

PO Box 3, Radcliffe New Road, Whitefield,
Manchester, M45 7NR, United Kingdom

Tel: +44 (0)845 345 5404

Fax: +44 (0)845 345 5406

Samples: +44 (0)845 345 5405

Email: info@cavaliofloors.com

www.cavaliofloors.com

CAVALIO POLSKA POLFLOR

Tel: +48 61 8203155

Email: info@cavaliofloors.pl

www.cavaliofloors.pl